SOUND LEVEL METER

PCE-324-ICA



- **automatic / manual measurement range selection**
- **fast and slow time weighting**
- **frequency weighting A and C**
- **numerical values and traffic light display**
- **measuring functions: MIN, MAX, HOLD**
- **automatic power off**
- **accuracy class 2**
- **incl. ISO-Calibration Certificate**

The sound level meter offers a wide measurement range of 30 to 130 dB (dBA) and 35 to 130 dB (dBC), making it suitable for accurate measurements in various acoustic environments. The accuracy of the device is ±1.5 dB at 94 dB @ 1 kHz. Equipped with functions for A and C frequency weighting and both fast and slow time weighting, our sound level meter is versatile and adaptable to different requirements.

The 2-inch LC colour display provides a clear and easy-to-read display of the measured values in numerical form. In addition, the device has a scale that enables a quick visual assessment of the sound level. With a sampling rate of 2 x per second, the sound level meter records acoustic changes almost in real time and is therefore particularly suitable for monitoring sound levels in dynamic environments.

The sound level meter is equipped with functions such as MIN, MAX and HOLD.

Specification

Sound level	
Measurement range up to	30 ... 130 dBA
Resolution	0,1 dB
Accuracy	±1.5 dB (94 dB @ 1 kHz) and ±5 dB (94 dB @ 8 kHz)
Sound level	
Measurement range up to	35 ... 130 dBC
Resolution	0,1 dB
Accuracy	±1.5 dB (94 dB @ 1 kHz) and ±5 dB (94 dB @ 8 kHz)
Sound level	
Measurement range up to	30 ... 80 dB
Resolution	0,1 dB
Accuracy	±1.5 dB (94 dB @ 1 kHz) and ±5 dB (94 dB @ 8 kHz)
Sound level	
Measurement range up to	60 ... 110 dB
Resolution	0,1 dB
Accuracy	±1.5 dB (94 dB @ 1 kHz) and ±5 dB (94 dB @ 8 kHz)
Sound level	
Measurement range up to	80 ... 130 dB
Resolution	0,1 dB
Accuracy	±1.5 dB (94 dB @ 1 kHz) and ±5 dB (94 dB @ 8 kHz)

General technical data	
Measuring functions	MIN, MAX, HOLD
Time weighting	fast (125 ms), slow (1 s)
Frequency weighting	A, C
Display type	LC colour display with backlight
Display size	2 Inch
Measuring rate	2 x per second
Microphone type	Condenser microphone
Standard(s)	IEC 61672-1 (Class II)
Automatic power-off	20 min
Automatic power-off can be deactivated	Yes
Tripod thread	1/4 inch
Menu language	English, English (GB)
Protection class (device)	IP20
(Rechargeable) battery	4 x 1,5 V AAA battery , Alkali-manganese
Capacity	1200 mAh
Operating conditions	0 ... 40 °C , 10 ... 80 % RH
Storage conditions	-10 ... 60 °C , 10 ... 70 % RH
Dimensions (L x W x H)	210 x 64 x 32 mm
Weight	123 g

PCE Instruments UK Ltd.
Chester Rd, Old Trafford Suite 1N-B, Trafford House, M32 0RS Manchester
Great Britain

Phone: +44 (0) 161 4649020
info@pce-instruments.co.uk