

PRODUCT SPECIFICATIONS

PERMANENT ROOF ANCHOR

The Permanent Roof Anchor is designed specifically for permanent use on wood rooftops. Manufactured with two alloy steel weather resistant D-Ring ends. This 18" long anchor is composed of stainless steel for an exceptionally long life. The Malta Dynamics Permanent Roof Anchor is 100% compliant with all applicable OSHA and ANSI regulations. The Permanent Roof Anchor is manufactured to be easy to install and is ideal for both residential construction and maintenance work.

This metal roof anchor features a 360 swivel top connection point to allow the user to enjoy complete freedom with their motions and can access all sides of the roof without having to reposition and without tangling. Because of the 360 anchor point, this anchor can withstand 5,000 lbs. of force in ALL directions. Get rid of the invasive and bulky anchors of the past and enjoy the ease and convenience of the Malta Dynamics Standing Seam Metal Roof Anchor.

KEY FEATURES

- Exclusive hole layout reduces damage to truss during install
 Reliable D-Ring anchor points
- Lightweight and durable
- Fasteners Included
- Can be installed with screws or nails

	PERFORMANCE SPECIFICATIONS		INS
		Worker Capacity Range	130-310 lbs. Max
		Minimum Breaking Strength	5,000 lbs. Max
		MATERIALS SPECIFICATIONS	
		Anchor	Alloy & Stainless Steel
		Screws	8 set grub screws (included)
		Length	18 inches
		FALL PROTECTION STANDARD	S
PACK	WEIGHT	OSHA 1926 Subpart M, 1910	
1	.9 lbs.	ANSI Z359.1:2007, A10.32-1	2
			Worker Capacity Range Minimum Breaking Strength MATERIALS SPECIFICATIONS Anchor Screws Length FALL PROTECTION STANDARD OSHA 1926 Subpart M, 1910

