

PRODUCT SPECIFICATIONS

HYBRID HOG® SELF-RETRACTING LIFELINES

The Malta Dynamics Hybrid Hog is a dual class SRL, engineered with the worker in mind. We've expertly designed one SRL that meets the rigorous standards of both OSHA and ANSI for SRL Class 1. A lower maximum arresting force significantly improves the safety factor of the device, and the MAF of the Hybrid Hog SRL is 900lbs! This compact, lightweight, and durable design makes transporting and storage easy, and it even comes with a convenient carry handle!

The Hybrid Hog retractable lifeline features 360° swivel top and bottom connection points to help save time and effort when clipping in and out. We know that working in the field can be hard on your equipment, so we've built this SRL with a galvanized steel cable and connectors. The connections and cable work in harmony with the housing to ensure a seam-lessly smooth payout and retraction. With proper care and inspections, you can keep your Hybrid Hog in action for years.

KEY FEATURES

PART #	SIZE	WEIGHT
C9000-G2	20'	11.3 lbs.
C9001-G2	30'	12.1 lbs.

- 1. Galvanized Steel Cable
- 2. Lightweight and Durable Housing
- **3.** Convenient Carry Handle
- 4. 360° Swivel Top
- 5. Steel Snap Hook
- Comes with Swivel Top and Bottom Connection Points
- Designed to lower impact force at impact
- RFID Chip
- Gripping Snout
- Side payout allows incredibly smooth cable payout and retraction
- Stackable design minimizes the space required for storage
- For overhead use only

PERFORMANCE SPECIFICATIONS

Worker Capacity Range	130-310 lbs. Max
Max Arresting Force	1,600 lbf
Average Arresting Force	900 lbf
Max Arresting Distance	24 in.

MATERIALS SPECIFICATIONS

Cable	Galvanized Steel
D-Rings/Buckles/Adjustments	Alloy Steel

FALL PROTECTION STANDARDS

ANSI	ANSI/ASSP Z359.14-2021
OSHA	1926 Subpart M, OSHA 1910, 1926.502, 1910.66