

DUAL SRL CONNECTOR

The High Strength Steel Locking Carabiner is designed to be durable and easy to use. Its ANSI standard tested gate is certified to withstand face and side loads up to 3,600 lbs. This carabiner is self-closing and self-locking and can be opened with just one hand. The locking d-shaped carabiner is made from heavy duty zinc plated alloy steel to make sure that this connector can stand up to the toughest environments while sustaining maximum grit. The zinc plating on this carabiner helps prolong the life of the connector and prevents rust and corrosion. The self-locking mechanism of this carabiner adds an extra level of security by requiring two actions to open the gate: twist the barrel and then pull the gate into an open position.



KEY FEATURES

1. Gate Opening is 2.13"

- Attach up to two self-retracting lifelines
- Maintain 100% Tie-Off
- Easy One-Hand Operation
- Heavy Duty Strength



PERFORMANCE SPECIFICATIONS

Worker Capacity Range	130-310 lbs. Max
Gate Strength	3,600 lbs.
Minimum Breaking Strength	5,000 lbs.

MATERIALS SPECIFICATIONS

Connector	Zinc Plated Alloy Steel
-----------	-------------------------

FALL PROTECTION STANDARDS

OSHA	1926
ANSI	Z359.12-2009 and A10.32-12

PART #

C1004

WEIGHT

.33 lbs.