

SimpleSight™ 5" LED Wireless Dual Channel Monitor

RVS-25WM

REAR VIEW
SAFETY
A Safe Fleet Brand



**NO INTERFERENCE
GUARANTEED**



Perfection takes time, especially with something as complicated as wireless transmission. Our newest wireless monitor, part of our new SimpleSight™ Series was born from years of testing and multiple prototypes. This monitor can receive a 100 ft. digital wireless signal from two SimpleSight™ wireless cameras, even at fast highway speeds! Pair this monitor with our compatible (**RVS-50W**), (**RVS-55W**), or (**RVS-65WP**) SimpleSight™ cameras without leaving the cab via Instant Pair technology.

Specifications

PANEL SIZE	5" LED DIGITAL PANEL	FREQUENCY	2400-2500MHZ
VIDEO SYSTEM	NTSC / PAL AUTO DETECTION	TRANSMISSION TYPE	DIGITAL WIRELESS
RESOLUTION	480 X 3 (RGB) X272	VIDEO INPUT	2 CHANNEL
BRIGHTNESS	450 CD/m ²	VIDEO SOURCE	1VP-P 75Ω
CONTRAST RATIO	500:1	AUTO PAIR	YES
SCREEN MODE	16:9	POWER CONSUMPTION	ABOUT 4W
FIELD OF VIEW	TOP 50°, BOTTOM 70°, L/R 70°	POWER SUPPLY	DC9-32V
DOT PITCH	0.077(W) × 0.231(H) MM	OPERATING TEMP.	-20°C ~ +70°C
ACTIVE AREA	110.000(W) × 62.832(H) MM	STORING TEMP.	-30°C ~ +80°C
POWER INPUT	DC10-32V		RH 90% MAX