

BACKUP CAMERA SYSTEM TWO CAMERA SETUP



NOTE: DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION

This 2 camera system is complete with a crystal clear 7" DIGITAL LED COLOR monitor with distance grid lines and mirror image capability, a power harness, two (2) 130° CCD cameras with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration rating (highest in the industry), and comes with a full year warranty.

System can be upgraded to the Quad View Monitor where a split screen (to view two cameras at the same time) is an option.

BACKUP CAMERA SYSTEM TWO CAMERA SETUP

RVS

A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" DIGITAL LED COLOR MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM COLOR CCD CAMERAS WITH A 130° VIEWING ANGLE
- 3 CHANNEL POWER HARNESS ALLOWING YOU TO CONNECT AN ADDITIONAL CAMERA
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING

NOTE: DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION



MONITOR

PANEL SIZE	7" LED DIGITAL PANEL
DOT RESOLUTION	800 X 3 (RGB) X 480
SCREEN MODE	16:9
CONTRAST RATIO	500:1:00
DISPLAY BRIGHTNESS	400CD/m ²
FIELD OF VIEW	U:50° D:60° L/R:70°
VIDEO INPUT	3 CHANNEL CVBS
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 9V-32V
AUDIO OUTPUT	0.5W
OPERATING TEMPERATURE	-20°C ~ +70° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	7" (L) X 5.25" (H) X 1" (D)
WEIGHT	400G
IMPACT RATING	5G
DOT PITCH	0.1926 (H) X 0.1710(V)
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES, PAL: 752(H) X 582 (V), NTSC: 811(H) X 507 (V)
LENS	2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX
NET WEIGHT	220Z