

<b>RLK8-520D4-A-NVR-Kit-IP-Camera-Specifications</b>			
	<b>Model</b>	<b>RLC-520A</b>	
<b>Note:</b>	The cameras of the kit cannot work without the NVR.		
<b>Video &amp; Audio</b>	Image Sensor	1/2.7" CMOS sensor	
	Video Resolution	Default: 2560 x 1920 (5.0 Megapixels) at 30 frames/sec	
	Lens	f=4.0mm fixed; F=2.0, with IR-cut filter	
	Video Format	H.264	
	Field of View	Horizontal: 80°	
		Vertical: 42°	
	Day & Night	Auto-switching with IR-cut filter	
Night Vision	30 meters (100ft) (LED: 18pcs/14mil/850nm)		
<b>Power</b>	Audio	Audio recording	
	PoE	IEEE 802.3af, 48V Active	
<b>Interface</b>	DC Power	DC 12.0V 1A, <12W	
	Power	DC power port	
	System	Reset button	
	Ethernet	One 10M/100Mbps; RJ45	
<b>Software Features</b>	Frame Rate	Mainstream: 2fps - 30fps (default: 30fps)	
		Substream: 4fps - 15fps (default: 10fps)	
	Code Rate	Mainstream: 1024Kbps - 8192Kbps (default: 6144Kbps)	
		Substream: 64Kbps - 512Kbps (default: 256Kbps)	
	Smart Alarm	Motion detection/Person detection/Vehicle detection	
Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording		
<b>Working Environment</b>	Temperature	Operating temperature: -10°C ~ +55°C (14°F ~ 131°F)	
	Humidity	Operating humidity: 10% ~ 90%	
<b>Size &amp; Weight</b>	Waterproof	IP66	
	Dimension	Φ105*95mm	
<b>Warranty</b>	Weight	467.5g	
	Limited Warranty	2-year limited warranty. For support, visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a>	