

## RLK8-800PT4

### Smart 8-Channel PoE Security Camera System with 4K UHD Pan & Tilt, Auto Tracking, Spotlight Night Vision, Smart Detection, 24/7 Recording & Two-Way Audio

- 360° Coverage with Auto Tracking
- 4K Color Night Vision
- Human/Vehicle/Animal Detection
- 8-Channel 2TB NVR



## Specifications

| Hardware               |                                                     |
|------------------------|-----------------------------------------------------|
| Hardware               | N7MB01                                              |
| Video/Audio Input      |                                                     |
| IP Video Input         | PoE IP Camera x 8                                   |
| Audio Input            | Cameras with built-in mic                           |
| Video/Audio Output     |                                                     |
| HDMI Output Resolution | 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 |
| VGA Output Resolution  | 1920x1080, 1280x1024, 1280x720, 1024x768            |
| Audio Output           | 1-Channel, RCA                                      |
| Decoding               |                                                     |
| Video Format           | H.264, H.265                                        |

|                               |                                                                                                                                              |
|-------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Live View/Playback Resolution | 7680×2160, 4608×1728, 4512×2512, 4096×3072, 3840×2160, 2560×2560, 2560×1920, 2560×1440, 2048×1536, 2304×1296, 1080p, 720p                    |
| Synchronous Playback          | Up to 4 channels                                                                                                                             |
| <b>HDD</b>                    |                                                                                                                                              |
| SATA                          | 1 x SATA interface (1 x 2TB HDD included)                                                                                                    |
| External HDD                  | 1 eSATA Interface for HDD                                                                                                                    |
| Capacity                      | Up to 16TB (max. 8TB capacity for each HDD)                                                                                                  |
| <b>External Interface</b>     |                                                                                                                                              |
| USB Interface                 | 2 x USB 2.0                                                                                                                                  |
| Network Interface             | 1, RJ-45 10/100 Mbps self-adaptive Ethernet interface for LAN/WAN<br>8, RJ-45 10/100 Mbps self-adaptive PoE Ethernet interface for IP camera |
| <b>PoE</b>                    |                                                                                                                                              |
| Max. Power Per Port           | 25W                                                                                                                                          |
| Supported Standard            | IEEE 802.3af/at                                                                                                                              |
| <b>Network</b>                |                                                                                                                                              |
| Network Protocols             | HTTP, TCP/IP, UDP, DHCP, P2P, UPNP, RTSP, SMTP, SSL/TLS, DNS, DDNS, NTP, FTP                                                                 |
| Browsers Supported            | Edge, Firefox, Chrome, Safari                                                                                                                |
| OS Supported                  | PC: Windows, Mac OS; smartphone: iOS, Android                                                                                                |
| Max. User Access              | 20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)                  |
| <b>General</b>                |                                                                                                                                              |
| Power Supply                  | DC 48V~53V                                                                                                                                   |
| Power Consumption             | <10W (Without HDD&PoE)                                                                                                                       |

|                     |                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Working Environment | Temperature: -10°C~+45°C (14°F~113°F);<br>humidity: 10%~90%                                                                                |
| Dimensions          | 260 x 41 x 230mm                                                                                                                           |
| Weight              | 1.4kg                                                                                                                                      |
| <b>Warranty</b>     |                                                                                                                                            |
| Limited Warranty    | 2-year limited warranty. For support,<br>visit <a href="https://support.reolink.com/hc/en-us/">https://support.reolink.com/hc/en-us/</a> . |

## Gallery & Specs



- 1. Bracket
- 2. Daylight sensor
- 3. 3000K warm light
- 4. Microphone
- 5. Lens
- 6. IR LEDs



- 1. Speaker
- 2. Heat dissipation holes
- 3. Reset hole
- 4. microSD card slot

