

# PRODUCT ID: 35620

## Outdoor Blank-out LED Backlit Sign

### MODEL

PHX1418GR-I942/120-277VAC



### DIMENSIONS

14" H x 18" W x 2.5" D (est. 6.121 lbs)

### CLASS

Class: PHX Series

Control Method: Switch (not included) or external relay.

### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

### MESSAGE

Color: Black opaque


Font: Swiss 721 Bold BT

Illumination: Backlit with high intensity LEDs. Message blanks out when off

Sign Messages: See message table below

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
SAFE TO ENTER	Green Wide Angle LED	1.5"	0.195-0.084
DANGER HIGH VOLTAGE TEST IN PROGRESS	Red Wide Angle LED	1.0"	0.131-0.057

NOTE: Above messages are independently controlled.

### Sample Display Options



### Frame Detail

