

## PRODUCT ID: 39004

### Outdoor LED Backlit Sign

#### MODEL

PHXF734W-D376/120-277VAC



#### DIMENSIONS

7" H x 34" W x 2.25" D (est. 6.948 lbs)

#### CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

#### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded all-weather frame, 2.25" deep.

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

#### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

#### MESSAGE

Color: Blue translucent

Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.


Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
EMPLOYEE PARKING	White Wide Angle LED	2.25"	0.347-0.150

NOTE: Above messages are independently controlled.

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

