

**PRODUCT ID: 39704**  
Outdoor Blank-out LED Backlit Sign

**MODEL**  
PHX718R-K193/120-277VAC



**DIMENSIONS**  
7" H x 18" W x 2.5" D (est. 4.242 lbs)

**CLASS**  
Class: PHX Series  
Control Method: Switch (not included) or external relay.

**CONSTRUCTION**  
Back Construction: 0.050" Lift-n-Shift Back  
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.  
Face Material: 1/8" thick, dark grey diffused acrylic  
Faces: Single Faced Sign  
Finish: Duranodic Bronze  
Graphic: Printed graphic applied to surface  
Mounting Channel: None

**ELECTRICAL**  
Flashing: Not Included  
Input Voltage: 120-277 VAC  
UL/cUL Listed: Listed for wet locations


**MESSAGE**  
Color: Black opaque  
Font: Swiss 721 Bold BT  
Illumination: Backlit with high intensity LEDs. Message blanks out when off  
Sign Messages: See message table below

| MESSAGE | LED/COLOR          | HEIGHT | AMPS        |
|---------|--------------------|--------|-------------|
| Booth 1 | Red Wide Angle LED | 2.875" | 0.131-0.057 |

NOTE: Above messages are independently controlled.

**Product View**

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



Frame Detail

