PRODUCT ID: 42276

Outdoor Blank-out LED Backlit Sign

MODEL

PHX1442WGR-L050/120-277VAC

DIMENSIONS

14" H x 42" W x 2.5" D (est. 14.697 lbs)

CLASS

Class: PHX Series
Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back
Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.
Face Material: 1/8" thick, dark grey diffused acrylic
Faces: Single Faced Sign
Finish: Duranodic Bronze
Graphic: Printed graphic applied to surface
Mounting Channel: None

ELECTRICAL

Flashing: Not Included
Input Voltage: 120-277 VAC
UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Black opaque
Font: Swiss 721 Bold BT
Illumination: Backlit with high intensity LEDs. Message blanks out when off
Sign Messages: See message table below

MESSAGE	LED/COLOR	HEIGHT	AMPS
CURRENCY EXCHANGE	White Wide Angle LED	3.75"	0.412-0.178
OPEN	Green Wide Angle LED	3.75"	0.217-0.094
CLOSED	Red Wide Angle LED	3.75"	0.144-0.062

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Sample Display Options



Frame Detail



09292021 | DP