

PRODUCT ID: 49884

Outdoor LED Backlit Sign

MODEL

PHXF1034DW-190RR/120-277VAC



DIMENSIONS

10" H x 34" W x 7.5" D (est. 25.092 lbs)

CLASS

CLASS: PHXF Series

Control Method: Switch (not included) or external relay.

CONSTRUCTION

Back Construction:

Cabinet: Mitered extruded aluminum frame with 2 hinged faces. LED displays installed with sign-in-sign construction. Moisture absorbent interior coating

Face Material: 1/8" thick, impact modified acrylic (0000)

Faces: Double Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

Mounting Channel: None

ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed for wet locations

MESSAGE

Color: Red translucent

Font: Swiss 721 Bold BT

Illumination: White high intensity LED backlit. Message always visible.

Sign Messages: See message table below


MESSAGE	LED/COLOR	HEIGHT	AMPS
EXIT	White Wide Angle LED	3.5"	0.477-0.207
EXIT	White Wide Angle LED	3.5"	0.477-0.207

NOTE: Above messages are independently controlled.

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.

Side A



Side B



Frame Detail

