

# PRODUCT ID: 50081

## Indoor Blank-out LED Backlit Sign

### MODEL

SBL2530RGRRR-B766/120-277VAC



### DIMENSIONS

25" H x 30" W x 2.5" D (est. 22.567 lbs)

### CLASS

Class: SBL Series

Control Method: Switch (not included) or external relay.

### CONSTRUCTION

Back Construction: 0.050" Lift-n-Shift Back

Cabinet: 1-piece, corrosion resistant, extruded aluminum frame, 2.5" deep.

Face Material: 1/8" thick, dark grey diffused acrylic

Faces: Single Faced Sign

Finish: Duranodic Bronze

Graphic: Printed graphic applied to surface

### ELECTRICAL

Flashing: Not Included

Input Voltage: 120-277 VAC

UL/cUL Listed: Listed

### MESSAGE

Color: Black opaque


Font: Swiss 721 Bold BT

Illumination: Backlit with LEDs. Message blanks out when off.

Sign Messages: See message table below

## Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



MESSAGE	LED/COLOR	HEIGHT	AMPS
BEAM OFF	Red Wide Angle LED	2.375"	0.065-0.028
BEAM ON	Green Wide Angle LED	2.375"	0.098-0.042
READY	Red Wide Angle LED	2.375"	0.065-0.028
X-RAY ON	Red Wide Angle LED	2.375"	0.065-0.028
GENERATOR ON	Red Wide Angle LED	2.375"	0.065-0.028

NOTE: Above messages are independently controlled.

### Sample Display Options



### Frame Detail

