



# TruTool TKA 1500

Technical data



**TruTool TKA 1500 without tool****TruTool TKA 1500 45° tool****MAXIMUM CHAMFER LENGTHS / MAXIMUM CHAMFER HEIGHTS**

Maximum chamfer length, steel 400 N/mm <sup>2</sup>	15 mm	15 mm
Maximum chamfer height, steel 400 N/mm <sup>2</sup>	10.6 mm	10.6 mm
Maximum chamfer length, steel 600 N/mm <sup>2</sup>	12 mm	12 mm
Maximum chamfer height, steel 600 N/mm <sup>2</sup>	8.5 mm	8.5 mm
Maximum chamfer length, steel 800 N/mm <sup>2</sup>	10 mm	10 mm
Maximum chamfer height, steel 800 N/mm <sup>2</sup>	7.1 mm	7.1 mm
Maximum chamfer length, aluminium 250 N/mm <sup>2</sup>	15 mm	15 mm
Maximum chamfer height, aluminium 250 N/mm <sup>2</sup>	10.6 mm	10.6 mm

**RADII**

Smallest inner radius	30 mm	30 mm
Smallest bore hole (Ø)	55 mm	55 mm

**GENERAL**

Minimum sheet thickness	3 mm + hs	3 mm + hs
Working speed (max.)	1.5 m/min	1.5 m/min
Nominal power consumption	2600 W	2600 W

**DIMENSIONS**

Length	679 mm	679 mm
Height	197 mm	197 mm

**WEIGHT**

Weight	10 kg	10 kg
--------	-------	-------